

BS 25 O.IH SAKT1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Fixing screws fix the short current bridge within the application. If the short current bridge is slided between two adjacent terminal blocks into the short circuit position, it can be fixed by means of a fastening screw. This ensures a permanent connection or short circuit.

General ordering data

Version	SAK Series, Set of fixings
Order No.	0334700000
Type	BS 25 O.IH SAKT1
GTIN (EAN)	4008190118839
Qty.	50 pc(s).

Creation date October 3, 2022 6:39:08 PM CEST

Catalogue status 23.09.2022 / We reserve the right to make technical changes.

BS 25 O.IH SAKT1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	28.7 mm	Depth (inches)	1.13 inch
Height	5.5 mm	Height (inches)	0.217 inch
Width	5.5 mm	Width (inches)	0.217 inch
Diameter	5.5 mm	Net weight	1.7 g

Temperatures

Storage temperature -25 °C...55 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1	SCIP	cabfa93a-285a-4cc9-a7cb-2feba00bc7a4
------------	----------------	------	--------------------------------------

Material data

Material	Steel, Brass	Colour	beige
----------	--------------	--------	-------

System specifications

Version for cross-connection link

Additional technical data

Installation advice	Direct mounting	Type of mounting	when screwed in
---------------------	-----------------	------------------	-----------------

Dimensions

Diameter 5.5 mm

General

Installation advice Direct mounting

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ECLASS 9.0	27-14-11-92
ECLASS 9.1	27-14-11-92	ECLASS 10.0	27-14-11-92
ECLASS 11.0	27-14-11-92	ECLASS 12.0	27-14-11-92

Approvals

ROHS Conform

Downloads

Engineering Data	EPLAN
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	