

## HDC 04A TOLU 1M20G

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

### General ordering data

|            |  |
|------------|--|
| Version    | HDC enclosures, Size: 1, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: M 20 |
| Order No.  | <a href="#">1788820000</a>   |
| Type       | HDC 04A TOLU 1M20G   |
| GTIN (EAN) | 4032248206360  |
| Qty.       | 1 pc(s).   |

## HDC 04A TOLU 1M20G

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 26.8 mm | Depth (inches)  | 1.055 inch |
| Height     | 50 mm   | Height (inches) | 1.969 inch |
| Width      | 36.5 mm | Width (inches)  | 1.437 inch |
| Net weight | 26 g    |                 |            |

## Temperatures

Limit temperature -40 °C ... 125 °C

## Environmental Product Compliance

REACH SVHC Lead 7439-92-1  
 SCIP d447edfa-0214-4f34-b5ba-82eae491b46a

| Chemical resistance | Substance         | Chemical resistance     |
|---------------------|-------------------|-------------------------|
|                     | Acetone           | Conditionally resistant |
|                     | Drilling oil      | Resistant               |
|                     | Diesel            | Resistant               |
|                     | Ethyl alcohol     | Resistant               |
|                     | Transmission oil  | Resistant               |
|                     | Hydraulic oil     | Resistant               |
|                     | Coolant           | Resistant               |
|                     | Petroleum benzine | Resistant               |
|                     | Sweat             | Resistant               |
|                     | Premium gasoline  | Conditionally resistant |
|                     | Water             | Resistant               |
|                     | UV                | Unstable                |
|                     | Ozone             | Unstable                |

## Dimensions

|                      |           |                     |         |
|----------------------|-----------|---------------------|---------|
| Cable entry          | w. thread | Height of housing B | 50 mm   |
| Total length housing | 26.8 mm   | Width housing C     | 26.8 mm |

## General data

|                   |                             |                       |                   |
|-------------------|-----------------------------|-----------------------|-------------------|
| EMC housings      | No                          | Housing main material | diecast aluminium |
| Protection degree | IP65 (in plugged condition) | Surface finish        | Powder coating    |
| Tightening torque | 0.5 Nm                      |                       |                   |

## HDC 04A TOLU 1M20G

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## Version

|                              |                                  |                                |                                    |
|------------------------------|----------------------------------|--------------------------------|------------------------------------|
| BG                           | 1                                | Cable entry                    | M 20 thread                        |
| Clamp version                | Side-locking clamp               | Colour (RAL)                   | RAL 7035                           |
| Design                       | Standard                         | Design of housing              | Cable entry from top, Plug housing |
| Design of locking system     | Side-locking clamp on lower side | Internal thread                | M 20                               |
| Number of cable entry on top | 1                                | Number of cable entry sideways | 0                                  |
| Size                         | 1                                | Size of cable entries          | M 20                               |
| Suitable for ModuPlug®       | No                               | Tightening torque              | 0.5 Nm                             |
| Top part/bottom part/lid     | upper part                       | Type                           | Plug                               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ECLASS 9.0  | 27-44-02-02 |
| ECLASS 9.1  | 27-44-02-02 | ECLASS 10.0 | 27-44-02-02 |
| ECLASS 11.0 | 27-44-02-02 | ECLASS 12.0 | 27-44-02-02 |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate No. (cURus) | E92202     |

## Downloads

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">CAD data – STEP</a>  |
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>   |
| Product Change Notification | <a href="#">20220214 Technical change to HDC housings</a><br><a href="#">20220214 Technische Änderung bei HDC-Gehäusen</a> |
| Technical Documentation     | <a href="#">1788820000 HDC_04A_TOLU_1M20G_STP_Blatt_1.pdf</a>  |
| Catalogues                  | <a href="#">Catalogues in PDF-format</a>   |
| Brochures                   | <a href="#">FL FIELDWIRING EN</a><br><a href="#">FL FIELDWIRING EN</a>   |

**Data sheet**

**HDC 04A TOLU 1M20G**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

