

## AP AKZ2.5 BL

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Product image



Similar to illustration

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

## General ordering data

|            |                                                      |
|------------|------------------------------------------------------|
| Version    | SAK Series, End plate, 2.5 mm, blue, Direct mounting |
| Order No.  | <a href="#">0697380000</a>                           |
| Type       | AP AKZ2.5 BL                                         |
| GTIN (EAN) | 4008 1900 18269                                      |
| Qty.       | 50 pc(s).                                            |

Creation date October 3, 2022 6:40:24 PM CEST

Catalogue status 23.09.2022 / We reserve the right to make technical changes.

## AP AKZ2.5 BL

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 21.5 mm | Depth (inches)  | 0.846 inch |
| Height     | 22.5 mm | Height (inches) | 0.886 inch |
| Width      | 2.5 mm  | Width (inches)  | 0.098 inch |
| Net weight | 0.78 g  |                 |            |

### Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C         |                                  |        |

### Material data

|                           |       |        |      |
|---------------------------|-------|--------|------|
| Material                  | PA 66 | Colour | blue |
| UL 94 flammability rating | V-2   |        |      |

### System specifications

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

### Additional technical data

|                     |                 |         |     |
|---------------------|-----------------|---------|-----|
| Installation advice | Direct mounting | Snap-on | Yes |
|---------------------|-----------------|---------|-----|

### General

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ETIM 8.0    | EC000886    | ECLASS 9.1  | 27-14-11-33 |
| ECLASS 10.0 | 27-14-11-33 | ECLASS 11.0 | 27-14-11-33 |
| ECLASS 12.0 | 27-14-11-33 |             |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |
| Brochures          |                                                 |