


Product data sheet

Characteristics

9422RQ1

Disconnect mechanism, circuit breaker, variable depth, 150/250A, 3 pole, operator only, for PowerPacT H and J breakers



Main

Range	9422R
Product	Circuit Breaker Mechanism
Mounting Type	Flange rod variable depth
Certifications	UL Recognized CSA
Circuit Breaker Type	MG-NSF 2 MG-NSF 3 PowerPact H or J 2 PowerPact H or J 3
Handle Type	Ordered separately

Ordering and shipping details

Category	21732-9422
Discount Schedule	CP1
GTIN	785901627319
Nbr. of units in pkg.	1
Package weight(Lbs)	3.82 lb(US) (1.733 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.50 in (13.97 cm)
Package 1 width	9.00 in (22.86 cm)
Package 1 Length	16.00 in (40.64 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------