



Main

Range of Product	Accessory
Product destination	Overload relay
Thermal overload type	Melting alloy

Complementary

[Ue] rated operational voltage	600 V AC
Height	1.87 in (47.6 mm)
Width	0.92 in (23.4 mm)
Depth	0.12 in (3 mm)

Ordering and shipping details

Category	21751-9998 DISCOUNT CP1
Discount Schedule	CP1
GTIN	785901862611
Nbr. of units in pkg.	1
Package weight(Lbs)	1.12 oz (31.8 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.30 in (3.3 cm)
Package 1 width	2.28 in (5.8 cm)
Package 1 Length	3.11 in (7.9 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.