# 9422CSF50

Disconnect mechanism, circuit breaker, cable operated, 150/250A, 3 pole, PowerPacT H and J breaker, 60 inch cable



#### Main

| Range   | 9422C                            |  |
|---------|----------------------------------|--|
| Product | Single Cable Operating Mechanism |  |

# Complementary

| Circuit Breaker Type | MG-NSF 2           |  |
|----------------------|--------------------|--|
| ••                   | MG-NSF 3           |  |
|                      | PowerPact H or J 2 |  |
|                      | PowerPact H or J 3 |  |
| Included             | Ordered separately |  |
| Number of Cables     | 1                  |  |
| Cable Length         | 60 in              |  |

## Ordering and shipping details

| 21732-9422             |   |
|------------------------|---|
| CP1                    |   |
| 785901104124           |   |
| 1                      |   |
| 5.90 lb(US) (2.676 kg) |   |
| Yes                    |   |
| MX                     |   |
|                        | CP1 785901104124 1 5.90 lb(US) (2.676 kg) Yes |

### **Packing Units**

| Unit Type of Package 1 | PCE                  |  |
|------------------------|----------------------|--|
| Package 1 Height       | 7.10 in (18.034 cm)  |  |
| Package 1 width        | 12.70 in (32.258 cm) |  |
| Package 1 Length       | 13.60 in (34.544 cm) |  |

#### Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
|---------------------------|---|
| REACh Regulation          | ☐REACh Declaration  |
| REACh free of SVHC        | Yes   |
| EU RoHS Directive         | Compliant EPEU RoHS Declaration   |
| Toxic heavy metal free    | Yes   |
| Mercury free              | Yes   |
|                           |   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| RoHS exemption information | ₽¥Yes                  |  |
|----------------------------|------------------------|--|
| China RoHS Regulation      | China RoHS Declaration |  |
| PVC free                   | Yes                    |  |
| Contractual warranty       |                        |  |
| Warranty                   | 18 months              |  |